Amendments to the Claims:

This listing of the claims will replace all prior versions, and listings, of claims in the application:

Listing of the Claims:

1. (previously amended) A method of measuring an absorbed dose of ionizing radiation using a measuring device that bears an integral identification mark, comprising the steps of:

providing a support;

coating on said support a first region for measuring an absorbed dose of ionizing radiation, said region comprising a binder and alanine;

disposing on said support a second region that bears an integral identification mark;

exposing at least the first region to a dose of ionizing radiation, wherein the alanine, upon exposure to ionizing radiation, produces radicals; and detecting the radicals in the first region.

- 2. (original) The method of claim 1 further comprising a step of revealing the identification mark in the second region.
- 3. (currently amended) The method of claim 1-or 2 further comprising a step of deciphering the identification mark in the second region.
- 4. (original) The method of claim 1 wherein the identification mark is a bar code, a series of alpha-numeric characters or a combination thereof.
- 5. (original) The method of claim 1 wherein the identification mark is on a substrate.
- 6. (original) The method of claim 5 wherein the substrate for the identification mark is a label.

- 7. (original) The method of claim 5 wherein the substrate for the identification mark is an intermediate layer and a dark-colored layer coated directly onto the support.
- 8. (original) The method of claim 1 wherein the substrate for the identification mark extends partially over the alanine-containing layer.
- 9. (currently amended) The method of claim <u>2</u>1 wherein the identification mark is <u>revealed</u> uneovered/revealed through the use of a laser.
- 10. (original) The method of claim 1 wherein the identification mark is printed onto a strip.

11 (canceled)

- 12. (previously amended) The method of claim 1 wherein the radicals remain stable for long periods of time.
- 13. (original) The method of claim 1 wherein the support is flexible.
- 14. (previously amended) The method of claim 1 wherein the alanine is in crystalline form.
- 15. (original) The method of claim 14 wherein the crystalline alanine comprises particles less than 100 microns in size.
- 16. (previously amended) The method of claim 1 wherein the coated first region is between 100 and 200 microns thick.
 - 17. (currently amended) A dosimeter comprising: a support;
- at least one first region disposed on said support, the first region containing alanine and a binder;

at least one second region disposed on said support; wherein the first region is <u>foreapable of</u> measuring an absorbed dose of ionizing radiation and the second region bears an identification mark on a substrate.

- 18. (previously presented) The dosimeter of claim 17 wherein the identification mark is a bar code, a series of alpha-numeric characters or a combination thereof.
- 19. (previously presented) The dosimeter of claim 17 wherein the substrate for the identification mark is a label.
- 20. (previously presented) The dosimeter of claim 17 wherein the substrate for the identification mark is a label which is adhered to the support by means of a thermally activated adhesive.
- 21. (previously presented) The dosimeter of claim 17 wherein the substrate for the identification mark is a label the topmost surface of which is coated with an intermediate layer and a dark-colored layer.
- 22. (previously presented) The dosimeter of claim 17 wherein the substrate for the identification mark is a label the topmost surface of which is coated with an intermediate layer and a dark-colored layer which is black.
- 23. (previously presented) The dosimeter of claim 17 wherein the substrate for the identification mark is an intermediate layer and a dark-colored layer coated directly onto the support.
- 24. (previously presented) The dosimeter of claim 17 wherein the substrate for the identification mark extends partially over the alanine-containing layer.
- 25. (previously presented) The dosimeter of claim 17 wherein the identification mark is uncovered/revealed through the use of a laser.

26. (previously presented) The dosimeter of claim 17 wherein the identification mark is printed onto a strip.